

NEXTECH

LT3508



Wall Mount Bracket

Suitable for STARLINK® GEN 3

Instruction Manual

Please read and save all instructions to ensure safe and effective use of this product.

BOX CONTENTS

1 x Wall Mount Bracket
1 x Pipe Adaptor

2 x Timber Studs
2 x Masonry Screws

6 x Mount Screws
1 x Allen Key

INSTALLATION

Internal Cable Routing



1. Choose this method if you prefer to connect the network cable after the mount has been installed.



2. Feed the network cable through the opening at the end of the wall mount arm.



3. Remove the four locking screws from the mounting tube.



4. Insert the mounting tube into the wall bracket.



5. Ensure the mounting tube clips securely into place.



6. Align the locating notch on the mounting tube with the matching notch on the wall bracket.



7. Feed the network cable through the mounting tube.



8. Connect the network cable to the Starlink® Gen 3.



9. Secure the wall bracket to a solid wall using the appropriate mounting hardware. The bracket may also be mounted directly to timber surfaces.



10. Slide the Starlink® Gen 3 onto the mounting tube until it locks into position.



11. Rotate the mounting tube to your preferred angle, then tighten the four locking screws.



12. Verify that all fasteners are secure and the installation is complete.

Direct Cable Connection



1. Choose this method for routing the network cable through the wall mount.



2. Feed the network cable through the opening at the end of the wall mount arm.



3. Continue feeding the cable through the arm until it exists from the mounting tube.



4. Remove the four locking screws from the mounting tube.



5. Insert the mounting tube into the wall bracket until it slides securely into place.



6. Reinstall and tighten the four locking screws.



7. Align the locating notch on the mounting tube with the matching notch on the wall bracket.



8. Continue feeding the network cable through the mounting tube.



9. Connect the network cable to the Starlink® Gen 3 socket.



10. Secure the wall bracket to a solid wall using the appropriate wall screws. It may also be mounted directly to timber surfaces.



11. Slide the Starlink® Gen 3 onto the mounting tube until it locks into position.



12. Rotate the mounting tube to your preferred angle, then tighten the four locking screws to secure it.

WARRANTY INFORMATION

Our product is guaranteed to be free from manufacturing defects for a period of 12 Months.

If your product becomes defective during this period, Electus Distribution will repair, replace, or refund where a product is faulty; or not fit for intended purpose.

This warranty will not cover modified product; misuse or abuse of the product contrary to user instructions or packaging label; change of mind and normal wear and tear.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and failure does not amount to a major failure.

To claim warranty, please contact the place of purchase. You will need to show receipt or other proof of purchase. Additional information may be required to process your claim.

Any expenses relating to the return of your product to the store will normally have to be paid by you.

The benefits to the customer given by this warranty are in addition to other rights and remedies of the Australian Consumer Law in relation to the goods or services to which this warranty relates.

This warranty is provided by: Electus Distribution
Address 46 Eastern Creek Drive, Eastern Creek NSW 2766
Ph. 1300 738 555