





Safety Data Sheet

1 – Product Identifier & Identity for the Chemical				
Manufacture	': WD-40 Company Australia Pty Ltd	Product Name: WD-40 Aerosol		
	-	Chemical Name: Mixture		
Address:	41 Rawson Street			
	(Level 2, Suite 23)	Product Use: Lubricant, Penetrant, Drives Out		
	Epping	Moisture, Removes and Protects Surfaces		
	NSW, 2121, Australia	From Corrosion		
Telephone:				
Information: +61 2 9868 2200		Restriction on Use: None Identified		
Emergency only: 1800 024 973				
5,	•	SDS Date Of Preparation: 5 July 2018		
Poisons Info	mation Centre:			
Australia: 13	11.26			
	: 0800 764 766			
How Loaland				
New Zealand	Contact Details:			
Name:	Eproducts New Zealand Limited			
Address:	7D Orbit Drive			
	Albany New Zealand			
Telephone:	-			
Information:	09 916 6750			
	····			

2 – Hazards Identification

Classification of the Hazardous Chemical (in accordance with WHS Regulation)

Health	Environmental	Physical
Aspiration Toxicity Category 1	Aquatic Acute Toxicity Category 3 Aquatic Chronic Toxicity Category 3	Flammable Aerosol Category 1 Gas Under Pressure: Compressed Gas

Label Elements



Contains: Naptha (Petroleum), hydrotreated heavy

Danger!

H222 Extremely flammable aerosol.

H280 Contains gas under pressure: may explode if heated.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

AUH066 Repeated exposure may cause skin dryness or cracking.

Prevention

P210 Keep away from heat, sparks, open flames and hot surfaces.-No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P273 Avoid release to the environment. **Response**P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor or physician.
P331 Do NOT induce vomiting. **Storage**P410+P412+P403 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Store in a well-ventilated place.
P405 Store locked up. **Disposal**P501 Dispose of contents and container in accordance with local and national regulations.

Other Hazards that do not Result in Classification: None

Ingredient	CAS #	Weight Percent	Substance Classification
Naptha (Petroleum), hydrotreated heavy	64742-48-9	50-60%	Flam. Liq. Cat 4 (H227) Asp. Tox. Cat 1 (H304) AUH066
Petroleum Base Oils	Mixture	<25%	Not Hazardous
Naphtha (petroleum),	64742-82-1	<10%	Flam. Liq. Cat 3 (H226)
hydrodesulfurized heavy	95-63-6		Asp. Tox. Cat 1 (H304)
(contains: 1,2,4-Trimethyl	108-67-8		Skin Irrit. Cat 2 (H315)
benzene, 1,3,5-Trimethyl	1330-20-7		STOT SE Cat 3 (H336)
benzene, Xylene, Mixed			Aq. Chronic Cat 2
Isomers)			(H411)
Carbon Dioxide	124-38-9	2-4%	Not Hazardous

3 - Composition/Information on Ingredients

See Section 16 for full text of GHS Classification and H phrases

4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call a Poisons Information Center (phone 13 11 26 from anywhere in Australia or 0800 764 766 in New Zealand) immediately.

Eye Contact: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Most Important Symptoms: Accidental ingestion may cause gastrointestinal effects with irritation, nausea, vomiting, dizziness, coma and death. Aspiration into the lungs during ingestion or vomiting may cause lung damage. Harmful or fatal if swallowed. May cause eye irritation. Skin contact may cause drying of the skin. Inhalation of mists may cause coughing, headache and dizziness.

Indication of Immediate Medical Attention and Special Treatment, if Needed: Immediate medical attention is required for ingestion.

5 – Fire Fighting Measures

Suitable Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire. **Specific Hazards Arising from the Chemical:** Extremely flammable aerosol. Contents under pressure. Keep away from ignition source and open fire. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Use shielding to protect against bursting containers. Cool fire-exposed containers with water.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Eliminate all sources of ignition and ventilate area. Wear appropriate protective clothing (see Section 8). **Environmental Precautions:** Avoid releases to the environment. Report spills to authorities as required.

Methods and Materials for Containment/Cleanup: Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Intentional misuse by deliberately concentrating vapors and inhaling can be harmful or fatal. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

Conditions for Safe Storage, including any incompatibilities: Store in a cool, dry ventilated area away from incompatible materials. Protect from physical damage. Do not store in direct sunlight, near open flames or above temperatures greater than 50°C.

Chemical	Occupational Exposure Limits	Biological Limit Value
Naphtha (petroleum), hydrodesulfurized heavy	1200 mg/m3 TWA (Total hydrocarbons) (manufacturer recommended) 5 mg/m3 TWA AU OEL (as oil mist, refined mineral) 5 mg/m3 TWA, 10 mg/m3 STEL NZ OEL (as oil mist, mineral) 5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)	None Established
Petroleum Base Oil	5 mg/m3 TWA AU OEL (as oil mist, refined mineral) 5 mg/m3 TWA, 10 mg/m3 STEL NZ OEL (as oil mist, mineral) 5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)	None Established
Naphtha (petroleum), hydrodesulfurized heavy	350 mg/m3 TWA (manufacturer recommended) 5 mg/m3 TWA AU OEL (as oil mist, refined mineral) 5 mg/m3 TWA, 10 mg/m3	None Established

8 – Exposure Controls /Personal Protection

	STEL NZ OEL (as oil mist, mineral) 5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)	
1,2,4-Trimethyl benzene	25 ppm TWA ACGIH TLV/AU/NZ OEL (as Trimethyl benzene, all isomers)	None Established
1,3,5-Trimethyl benzene	25 ppm TWA ACGIH TLV/AU/NZ OEL (as Trimethyl benzene, all isomers)	None Established
Xylene, Mixed Isomers	80 ppm TWA, 150 ppm STEL AU OEL 50 ppm TWA NZ OEL 100 ppm TWA, 150 ppm STEL ACGIH TLV	Methylhippuric acids in urine, End of shift, 1.5 g/g creatinine.
Carbon Dioxide	5000 ppm TWA, 30000 ppm STEL ACGIH TLV/AU/NZ OEL	None Established

The Following Controls are Recommended for Normal Consumer Use of this Product Appropriate Engineering Controls: Use in a well-ventilated area. Personal Protection:

Eye Protection: Avoid eye contact. Always spray product away from your face.

Skin Protection: Avoid prolonged or repeated skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended Appropriate Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear an approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Work/Hygiene Practices: Eye wash facilities should be available. Wash hands after handling. Other Protective Equipment: None required.

Appearance and Odor:	Aerosol spray with a	Partition Coefficient of	Not determined
	strong citrus odor	n-octanol/water:	
Odor Threshold:	Not determined	Auto-ignition temperature:	Not determined
pH:	Not determined	Decomposition Temperature:	Not determined
Melting/Freezing Point:	Not applicable	Viscosity:	Not determined
Boiling Point / Range:	162-192°C (324-378°F) (Naphtha (petroleum), hydrodesulfurized heavy)	Specific Heat Value:	Not determined
Flash Point:	58°C (136.4°F) (concentrate)	Particle Size:	Not applicable
Evaporation Rate (Butyl Acetate = 1):	Not determined	VOC:	Not determined
Flammability (solid, gas):	Not applicable	Percent Volatile:	Not determined
Flammable Limits:	LEL 0.6% UEL 9.0%	Saturated Vapor	Not determined

9 – Physical and Chemical Properties

	(Naptha (Petroleum), hydrotreated heavy)	Concentration:	
Vapor Pressure:	Not determined	Release of invisible flammable vapors and gases:	Yes
Vapor Density (air = 1):	Not determined	Aerosol Protection Level (NFPA 30B):	3
Relative Density (Water = 1):	Not determined	Solubility:	Insoluble in water

10 – Stability and Reactivity

Reactivity: Non-reactive

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Avoid extreme heat, flames and other sources of ignition. Avoid physical damage to aerosol can.

Incompatible Materials: Oxidizing agents, mineral acids, halogenated organic compounds. **Hazardous Decomposition Products:** Oxides of carbon and nitrogen, and unburned hydrocarbons.

11 – Toxicological Information

Health Hazards:

Ingestion: Swallowing is an unlikely route of exposure for an aerosol product. Swallowing large amounts may produce gastrointestinal irritation, nausea, vomiting and diarrhea. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Eye Contact: Liquid sprayed into eyes may cause irritation. May cause redness, stinging, swelling, and tearing.

Skin Contact: May produce mild skin irritation. Prolonged and/or repeated contact may cause defatting with possible dermatitis.

Inhalation: Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Chronic Exposure: None known.

Medical Conditions Aggravated by Exposure: Preexisting eye, skin and respiratory conditions may be aggravated by exposure.

Acute Toxicity Values:

Naptha (Petroleum), hydrotreated heavy: Oral rat LD50- >5000 mg/kg, Skin rat LC50- 4951 mg/kg

Naphtha (petroleum), hydrodesulfurized heavy: Oral rat LD50- >2000 mg/kg, Skin rat LD50- >2000 mg/kg.

Skin Corrosion/Irritation: No data available for mixture. Based on the ingredients, this product is not expected to be a skin irritation.

Serious Eye Damage/Irritation: No data available for mixture. Based on the ingredients, this product is not expected to be an eye irritant.

Respiratory or Skin Sensitization: This product is not expected to cause sensitization.

Germ Cell Mutagenicity: None of the components have been found to be mutagenic.

Carcinogenicity: None of the components are listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH, US OSHA or the EU CLP.

Reproductive Toxicity: None of the components are known to cause adverse reproductive effects.

Specific Target Organ Toxicity:

Single Exposure: No data available.

Repeated Exposure: No data available.

Aspiration Hazard: Based on the ingredients, this product is expected to present an aspiration hazard and may be harmful if the contents are swallowed.

12 – Ecological Information

Ecotoxicity:

Naphtha (petroleum), hydrodesulfurized heavy: 96hr LL50 Rainbow trout-10-30 mg/L, 48hr EL50 Daphnia magna- 10-22 mg/L

This product has been classified as harmful to the aquatic environment with long lasting effects based on the components. Releases to the environment should be avoided.

Persistence and Degradability: Naphtha (petroleum), hydrodesulfurized heavy: Readily biodegradable. Bioaccumulative Potential: No data available. Mobility in Soil: No data available. Other Adverse Effects: None Known

13 - Disposal Considerations

Safe Handling and Disposal Method: Aerosol containers should not be punctured, compacted in home trash compactors or incinerated.

Disposal of Contaminated Packaging: Empty containers may be disposed of through normal waste management options.

Environmental Regulations: Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations.

14 – Transportation Information

IMDG Shipping Name: Aerosols IMDG Hazard Class: 2.1 UN Number: UN1950 Marine Pollutant: No

IATA Shipping Name: Aerosols, Flammable IATA Hazard Class: 2.1 UN Number: UN1950

ADG Shipping Name: Aerosols ADG Hazard Class: 2.1 UN Number: UN1950 Hazchem (Emergency Action) Code: 2YE

Special Precautions for User: WD-40 Company does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

15 – Regulatory Information

Montreal Protocol (Ozone Depleting Substances): None present The Stockholm Convention (Persistent Organic Pollutants): None present The Rotterdam Convention (Prior Informed Consent): Not applicable Basel Convention: Not applicable International Convention for the Prevention of Pollution from Ships (MARPOL): 1, 2, 4-Trimethyl benzene and 1, 3, 5-Trimethyl benzene are listed.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Not applicable

Australian Inventory of Chemical Substances: All of the components of this product are listed on the AICS inventory.

New Zealand:

HSNO Approval Number: HSR002515

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Good for transport purposes.

HSNO Hazard Classes: 2.1.2A, 6.1E, 9.1D, 9.1C

New Zealand Inventory: All the ingredients comply with the HSNO regulations.

16 – Other Information

REVISION DATE: <u>5 July 2018</u>

SUPERSEDES: 23 July 2015

Prepared By: Industrial Health & Safety Consultants, Inc.

Full Text of GHS Classification and H Phrases from Section 3: Ag. Chronic Cat 2 Aquatic Chronic Toxicity Category 2 Asp. Tox. Cat 1 Aspiration Toxicity Category 1 Flam. Liq. Cat 3 Flammable Liquid Category 3 Flam. Lig. Cat 4 Flammable Liquid Category 4 Skin Irrit. Cat 2 Skin Irritant Category 2 STOT SE Cat 3 Specific Target Organ Toxicity Single Exposure Category 3 H226 Flammable liquid and vapor. H227 Combustible liquid. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. AUH066 Repeated exposure may cause skin dryness or cracking. List of Abbreviations or Acronyms: ACGIH American Conference of Industrial Hygienists ADG Australian Dangerous Goods AICS Australian Inventory of Chemical Substances AU Australia EC Effective Concentration EU European Union GHS Globally Harmonized System of Classification and Labelling of Chemicals HSNO Hazardous Substances and New Organisms IARC International Agency of Research on Cancer IATA International Air Transport Association IMDG International Maritime Dangerous Goods LC Lethal Concentration LD Lethal Dosage LEL Lower Explosive Limit NTP National Toxicology Program **OEL Occupational Exposure Limits** US OSHA United States Occupational Safety and Health Administration PEL Permissible Exposure Limit SDS Safety Data Sheet STEL Short Term Exposure Limit TWA Time-Weighted Average

UEL Upper Explosive Limit VOC Volatile Organic Compounds WHS Work Health and Safety

REVIEWED BY: <u>I. Kowalski</u>

TITLE: Manager Regulatory Affairs

This SDS complies with Australian guidelines for SDS. The foregoing information has been compiled from sources believed to be accurate but is not warranted to be. Recipients are advised to confirm in advance of need that data is correct. Standards change without notice. It is the responsibility of the recipient to insure that their personnel have been notified of any changes which may affect them. The data provided on this SDS are not meant to be used as specifications, only as guideline information as to the safe use of this product. User should refer to applicable laws before use.

1042400/ No.0096103